

DEXCOWIN®



**THE LEADER IN PORTABLE X-RAYS AND
DIGITAL SENSORS INNOVATIONS**

REX² PREMIUM

(Digital Intra Oral Sensor CMOS)

THREE SIZES ARE AVAILABLE

Adult



Universal



Pedo



Enhanced Cable Durability



Thinner Than Competitors'



Waterproof

USB Direct Interface



Molding Type USB Connector

Why Should I Go Digital?

SAVE MONEY

Huge overall saving by dispensing with the cost and hassle of periodic film and developing chemical purchases.

SAVE SPACE

Do away with valuable real estate taken up by dark rooms and increase overall productivity.

SAVE TIME

No more time spent needlessly developing film. Instant exposure allows you to immediately diagnose your patient.

MORE TIME FOR PATIENTS EQUALS MORE BUSINESS FOR YOU!

Why Pay more for less?

- › **MUCH CHEAPER** - Half price (50%) with same image quality.
- › **EXTREMELY HIGHEST RESOLUTION** - Never lost competition of quality.
- › **MORE SAFETY** - Highly sensitive to low amount of radiation dose.
- › **ASSURED CABLE DURABILITY** - 25K Times Cable Bending Test.
- › **HIGH COMPATIBILITY** - With Most software in market.
- › **LOW MAINTENANCE COST** - Signature customer support.

One Click FMX

Compatibility with your software

- › Provide full range of function for your own software
- › Auto series shots function
 - › Select all objected teeth prior to series shot
 - › Keep shooting teeth without setting for each time
 - › Images will be stored to the selected folder in order
- › Applicable to
 - › Dexis sensor users
 - › Schick sensor users
 - › Suni sensor users
 - › XDR sensor users
 - › Gendex Vixwin sensor users
- › No need to buy a new software but sensor only
 - › Stay with the familiar and practiced software

Same Size with Dexis



SPECIFICATION

- > Sensor Typr : CMOS
- > Scintillator Csl : TL with FOP
- > Active Area :
- > 20 X 30 / 24 x 33 / 26 x 36 mm
- > Pixel Pitch :29.6 μm
- > Line pair : 18 lp/mm
- > A/D Conversion 12 bits
- > Interface : Direct USB 2.0
- > Waterproof : IP68
- > Energy Range 50~100 kV
- > Dimension(W x L x H) :
- > 25.4 X 37.6 X 4.8 mm (1.0)
- > 29.2 x 39.5 x 4.8 mm (1.5)
- > 31.5 x 42.8 x 4.8 mm (2.0)
- > Weight Cable Length : 2.7m

WARRANTY PLAN

- > 1 year manufacturer warranty
- > 5 years reduced cost replacement plan



Dexcowin Global Inc.
155 N. Lake Ave. Suite 800 Pasadena. CA 91101
Tel: 626 993 6716 Fax 626 993 6601
info@dexcowin.com

DEXCOWIN[®]